

Samsung Portable SSD T7 Shield

2022 Data Sheet

Revision 2.0



DISCLAIMER

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein may change without notice and is provided on an “AS IS” basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppels or otherwise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung office (www.samsung.com/ssd and www.samsung.com/support). All brand names, trademarks and registered trademarks belong to their respective owners.

COPYRIGHT © 2022

This material is copyrighted by Samsung Electronics. Any unauthorized reproductions, use or disclosure of this material, or any part thereof, is strictly prohibited and is a violation under copyright law.

Technical Specifications

Samsung Portable SSD T7 Shield			
Interface	USB 3.2 Gen2 (10Gbps)		
Hardware Information	Capacities	1TB/2TB/4TB ¹	
	Dimensions	59 x 88 x 13mm	
	Weight	98 grams ²	
Performance	Sequential Read	Up to 1,050 MB/sec ³	
	Sequential Write	Up to 1,000 MB/sec ³	
Durability	Water/Dust Resistant	IP 65 ⁴	
	Drop Resistant	Up to 3m ⁵	
Security	Encryption	AES 256-bit hardware encryption	
	Software	Samsung Portable SSD 1.0 ⁶ Samsung Magician Software	
Reliability	Temperature	Operating	0°C to 60°C ⁷
		Non-Operating	-40°C to 85°C
	Humidity		5% to 95% non-condensing
	Shock	Non-Operating	1,500G, duration: 0.5ms, 3 axis
	Vibration	Non-Operating	20~2,000Hz, 20G
Certifications		CE, BSMI, KC, VCCI, C-tick, FCC, IC, UL, TUV, CB, EAC, UKCA, BIS	
RoHS Compliance		RoHS 2	
Warranty		Three (3) Year Limited Warranty	

1 GB=1,000,000,000 bytes, 1 TB=1,000,000,000,000 bytes. Lower capacity may be demonstrated by your computer due to use of a different measurement standard.

2. Exact weight of product may vary by capacity.

3 Max data transfer speed is measured based on Samsung's internal testing standards with the enclosed cable. Performance may vary depending on host configuration, cable and user system environment.

4. This device has a IP65 rating based on internal testing conducted under controlled conditions. Water and dust resistance capabilities may vary depending on the actual environmental conditions. Damage caused by liquid and dust are not covered under warranty.

***IPX5 Test condition: Device was exposed to fresh water projected from a nozzle (Φ6.3mm) 3 meters away at 12.5 l/min for 3 minutes.

****IP6X Test condition: Device was exposed to 2kg/m³ of active dust with a pressure under 2kPa for 8 hours in a vacuum chamber.

5. The drop test was conducted under controlled conditions. Drop resistance may vary depending on the actual environmental conditions. Damage caused by drop is not covered under warranty.

*Test condition: Device was dropped free-fall to a metal plate from 3-meter height.

6. T7 Series Software's minimum System Requirements : Windows 7 or higher, Mac OS X 10.10 or higher, Android Lollipop or higher

7. Tc is measured at the hottest point on the case. Sufficient airflow is recommended to be operated properly on heavier workload within device operating temperature."

PRODUCT LINE-UP

Density	Model Name	Model Code	Box Contents
4TB	MU-PE4T0	MU-PE4T0S/WW	<ul style="list-style-type: none"> • Samsung Portable SSD T7 Shield • USB Type-C to C, Type-C to A cables • Quick User Manual & Warranty Statement
		MU-PE4T0S/AM	
		MU-PE4T0S/EU	
2TB	MU-PE2T0	MU-PE2T0S/WW	
		MU-PE2T0K/WW	
		MU-PE2T0R/WW	
		MU-PE2T0S/AM	
		MU-PE2T0K/AM	
		MU-PE2T0R/AM	
		MU-PE2T0S/EU	
		MU-PE2T0K/EU	
		MU-PE2T0R/EU	
1TB	MU-PE1T0	MU-PE1T0S/WW	
		MU-PE1T0K/WW	
		MU-PE1T0R/WW	
		MU-PE1T0S/AM	
		MU-PE1T0K/AM	
		MU-PE1T0R/AM	
		MU-PE1T0S/EU	
		MU-PE1T0K/EU	
		MU-PE1T0R/EU	