

## Eaton 5PX1500IRTNG2



Eaton 5PX Gen2 UPS, 1500 VA, 1500 W,  
Input: C14, Output: (8) C13, Rack/tower, 2U,  
Network card included

Imaginile sunt doar cu titlu informativ



### Specificații generale

**PRODUCT NAME** Eaton 5PX Gen2 UPS

**CATALOG NUMBER** 5PX1500IRTNG2

**UPC** 743172104755

**PRODUCT LENGTH/DEPTH** 448 mm

**PRODUCT HEIGHT** 85.5 mm

**PRODUCT WIDTH** 438 mm

**PRODUCT WEIGHT** 22.4 kg

**COMPLIANCES** IEC/EN 62040-1  
IEC/EN 62040-2  
IEC/EN 62040-3  
RoHS Compliant  
REACH  
UL 1778  
CSA 22.2

**CERTIFICATIONS** CE  
cTUVus  
EAC  
Cm  
UKCA  
Ukr  
KCC  
ENERGY STAR certified

**MODEL CODE** Eaton 5PX 1500i RT2U  
Netpack G2

## Informații suplimentare

<b>AUTO SHUTDOWN FUNCTION</b>	Yes
<b>COLOR</b>	Black/silver
<b>CONSTRUCTION TYPE</b>	482.6 mm (19 inch) device
<b>EFFICIENCY AT MAX. LOAD</b>	98
<b>ENCLOSURE</b>	Black/silver
<b>PACKAGE CONTENTS</b>	<ul style="list-style-type: none"><li>• Network Management Card</li><li>• Rack-mounting kit</li><li>• (2) Supports for tower mounting</li><li>• Cable locking system</li><li>• USB cable</li><li>• Serial cable</li><li>• (2) IEC-IEC cables</li><li>• Quickstart guide</li><li>• Safety instructions</li></ul>
<b>PHASE (INPUT)</b>	1
<b>PHASE (OUTPUT)</b>	1
<b>RACK MOUNTING KIT</b>	Yes

## Battery specifications

<b>BATTERY MANAGEMENT</b>	ABM & Temperature compensated charging method (user selectable), Automatic battery test, deep discharge protection, automatic recognition of external battery units
<b>BATTERY QUANTITY</b>	4
<b>BATTERY RATING</b>	12 V / 9 Ah
<b>BATTERY REPLACEMENT</b>	User replaceable
<b>BATTERY TYPE</b>	Lead-acid maintenance-free (replaceable)
<b>EXTENDED BATTERY CAPABILITY</b>	Yes
<b>RUNTIME GRAPH</b>	<a href="#">View runtime graph</a>

## Comunicație

<b>COMMUNICATION</b>	<ul style="list-style-type: none"><li>• USB port (HID compliant)</li><li>• Serial port (RS232)</li><li>• Mini-terminal block for remote On/Off and Remote Power Off</li><li>• Mini-terminal block for output relay</li><li>• Dry contacts (3 outputs, 1 input, optocoupler, DB9)</li></ul>
----------------------	--

<b>EXPANSION SLOTS</b>	One slot, network card included
<b>INCLUDES NETWORK CARD</b>	Yes
<b>POTENTIAL FREE SWITCH CONTACT</b>	Yes
<b>SOFTWARE COMPATIBILITY</b>	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
<b>TYPE OF INTERFACE</b>	LCD Display with blue backlight
<b>USER INTERFACE</b>	Multilingual graphical LCD display

## Ieșire electrică

<b>FEED TYPE</b>	1
<b>OUTPUT NOMINAL VOLTAGE</b>	230V default (200/208/220/230/240V)
<b>OUTPUT POWER FACTOR</b>	1
<b>OUTPUT VOLTAGE RANGE</b>	230 V (+6%/-10%)
<b>OUTPUT WAVEFORM</b>	Sine wave
<b>RECEPTACLE</b>	(8) C13
<b>TOPOLOGY</b>	Line-interactive
<b>VA RATING</b>	1500 VA
<b>VOLTAGE</b>	230V
<b>VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX</b>	0
<b>WATTAGE</b>	1500 W

## Intrare electrică

<b>INPUT CONNECTION</b>	C14
<b>INPUT FREQUENCY RANGE</b>	47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode
<b>INPUT NOMINAL VOLTAGE</b>	230V default (200/208/220/230/240V)
<b>INPUT VOLTAGE RANGE</b>	160-294 V (adjustable to 150 V-294 V)
<b>NOMINAL FREQUENCY</b>	50-60 Hz

## Mediu

<b>ALTITUDE</b>	3000 m
<b>NOISE LEVEL</b>	<40 dB at 1 meter
<b>RELATIVE HUMIDITY</b>	0-90% non-condensing
<b>TEMPERATURE RANGE</b>	0° to 40°C (32° to 104°F), batteries recommended max. 25°C (77°F)

## Resurse

COMPLIANCE INFORMATION [Eaton 5PX Gen2 - EU Declaration of Conformity](#)

GHIDURI DE UTILIZARE [Eaton 5PX Gen2 - Quickstart guide](#)

PEP ECO-PASSPORT [eaton-industry-standard-network-ups-pep-eaton-00395-v0101-en.pdf](#)

---

**DENUMIREA PROIECTULUI:**

**NUMĂRUL PROIECTULUI:**

**PREGĂTIT DE:**

**DATA:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Irlanda  
Eaton.com

© 2026 Eaton. Toate drepturile rezervate

Urmăriți-ne pe rețelele de socializare pentru a obține cele mai noi informații despre produse și asistență.

